

Listing of the Claims

1 (Original). A sheet feeding apparatus comprising:

- a sheet container for containing a plurality of stacked sheets;
- an elevation/lowering driving unit for elevating and lowering the sheet container;
- a sheet conveying unit for sequentially taking out the sheets from an uppermost layer put in contact with the sheet conveying unit by elevating the sheet container by the elevation/lowering driving unit and conveying the sheets to a predetermined conveyance path;
- a regulating unit provided so as to be slidable on the sheet container for regulating a set position of a sheet;
- a position detector for detecting a position of the regulating unit; and
- a contact detector for detecting a contact state between the uppermost layer of the sheets contained in the sheet container and the sheet conveying unit,

wherein the elevation/lowering driving unit lowers the sheet container when a change in the position of the regulating unit is detected by the position detector in a state in which the uppermost layer of the sheets contacts the sheet conveying unit.

2 (Original). The sheet feeding apparatus according to Claim 1, wherein the elevation/lowering driving unit lowers the sheet container until the uppermost layer of the sheets and the sheet conveying unit are separated when the position detector detects a change in the position of the regulating unit.

3 (Original). The sheet feeding apparatus according to Claim 1, further comprising:

- a receiving unit for receiving information according to a lowered amount of the sheet container; and
- a storage for storing the received information,

wherein the elevation/lowering driving unit lowers the sheet container by the lowered amount stored in the storage when the position detector detects a change in the position of the regulating unit.

4 (Original). The sheet feeding apparatus according to Claim 1, further comprising a measuring unit for measuring a dimension of a sheet contained in the sheet container based on a detection result of the position detector.

5 (Original). The sheet feeding apparatus according to Claim 1, further comprising a clocking unit, wherein the elevation/lowering driving unit elevates the sheet container when a change in the position of the regulating unit is not detected for a predetermined time.

6 (Original). A sheet feeding apparatus comprising:

- sheet containing means for containing a plurality of stacked sheets;
- elevation/lowering driving means for elevating and lowering the sheet containing means;
- sheet conveying means for sequentially taking out the sheets from an uppermost layer put in contact with the sheet conveying means by elevating the sheet containing means by the elevation/lowering driving means and conveying the sheets to a predetermined conveyance path;
- regulating means provided so as to be slidable on the sheet containing means for regulating a set position of a sheet;
- position detecting means for detecting a position of the regulating means; and
- contact detecting means for detecting a contact state between the uppermost layer of the sheets contained in the sheet containing means and the sheet conveying means,

wherein the elevation/lowering driving means lowers the sheet containing means when a change in the position of the regulating means is detected by the position detecting means in a state in which the uppermost layer of the sheets contacts the sheet conveying means.

7 (Original). The sheet feeding apparatus according to Claim 6, wherein the elevation/lowering driving means lowers the sheet containing means until the uppermost layer of the sheets and the sheet conveying means are separated when the position detecting means detects a change in the position of the regulating means.

8 (Original). The sheet feeding apparatus according to Claim 6, further comprising:
receiving means for receiving information according to a lowered amount of the sheet containing means; and
storing means for storing the received information,
wherein the elevation/lowering driving means lowers the sheet containing means by the lowered amount stored in the storing means when the position detecting means detects a change in the position of the regulating means.

9 (Original). The sheet feeding apparatus according to Claim 6, further comprising measuring means for measuring a dimension of a sheet contained in the sheet containing means based on a detection result of the position detecting means.

10 (Original). The sheet feeding apparatus according to Claim 6, further comprising clocking means, wherein the elevation/lowering driving means elevates the sheet containing means when a change in the position of the regulating means is not detected for a predetermined time.

11 (Original). An image reading apparatus comprising:
a sheet container for containing a plurality of stacked sheets;
an elevation/lowering driving unit for elevating and lowering the sheet container;
a sheet conveying unit for sequentially taking out the sheets from an uppermost layer put in contact with the sheet conveying unit by elevating the sheet container by the elevation/lowering driving unit and conveying the sheets to a predetermined conveyance path;
an image reading unit for reading an image on a sheet conveyed by the sheet conveying unit;
a regulating unit provided so as to be slidable on the sheet container for regulating a set position of a sheet;
a position detector for detecting a position of the regulating unit; and
a contact detector for detecting a contact state between the uppermost layer of the sheets contained in the sheet container and the sheet conveying unit,

wherein the elevation/lowering driving unit lowers the sheet container when a change in the position of the regulating unit is detected by the position detector in a state in which the uppermost layer of the sheets contacts the sheet conveying unit.

12 (Original). The image reading apparatus according to Claim 11, wherein the elevation/lowering driving unit lowers the sheet container until the uppermost layer of the sheets and the sheet conveying unit are separated when the position detector detects a change in the position of the regulating unit.

13 (Original). The image reading apparatus according to Claim 11, further comprising:

- a receiving unit for receiving information according to a lowered amount of the sheet container; and

- a storage for storing the received information,

- wherein the elevation/lowering driving unit lowers the sheet container by the lowered amount stored in the storage when the position detector detects a change in the position of the regulating unit.

14 (Original). The image reading apparatus according to Claim 11, further comprising a measuring unit for measuring a dimension of a sheet contained in the sheet container based on a detection result of the position detector.

15 (Original). The image reading apparatus according to Claim 11, further comprising a clocking unit, wherein the elevation/lowering driving unit elevates the sheet container when a change in the position of the regulating unit is not detected for a predetermined time.

16 (Original). An image forming apparatus comprising:

- a sheet container for containing a plurality of stacked sheets;

- an elevation/lowering driving unit for elevating and lowering the sheet container;

a sheet conveying unit for sequentially taking out the sheets from an uppermost layer put in contact with the sheet conveying unit by elevating the sheet container by the elevation/lowering driving unit and conveying the sheets to a predetermined conveyance path;

an image forming unit for forming an image on a sheet conveyed by the sheet conveying unit;

a regulating unit provided so as to be slidable on the sheet container for regulating a set position of a sheet;

a position detector for detecting a position of the regulating unit; and

a contact detector for detecting a contact state between the uppermost layer of the sheets contained in the sheet container and the sheet conveying unit,

wherein the elevation/lowering driving unit lowers the sheet container when a change in the position of the regulating unit is detected by the position detector in a state in which the uppermost layer of the sheets contacts the sheet conveying unit.

17 (Original). The image forming apparatus according to Claim 16, wherein the elevation/lowering driving unit lowers the sheet container until the uppermost layer of the sheets and the sheet conveying unit are separated when the position detector detects a change in the position of the regulating unit.

18 (Original). The image forming apparatus according to Claim 16, further comprising:

a receiving unit for receiving information according to a lowered amount of the sheet container; and

a storage for storing the received information,

wherein the elevation/lowering driving unit lowers the sheet container by the lowered amount stored in the storage when the position detector detects a change in the position of the regulating unit.

19 (Original). The image forming apparatus according to Claim 16, further comprising a measuring unit for measuring a dimension of a sheet contained in the sheet container based on a detection result of the position detector.

20 (Original). The image forming apparatus according to Claim 16, further comprising a clocking unit, wherein the elevation/lowering driving unit elevates the sheet container when a change in the position of the regulating unit is not detected for a predetermined time.